

Meditec 1200

Portable Emergency Ventilator







Technical Specifications

Pneumatically Driven Ventilator	✓
Driven from pipeline or cylinder operated with an automatic switch-over valve	✓
IPPV Ventilation Mode	✓
Adult & Pediatric	✓
Manual Override Function	✓
Bronchial Suction	✓
In-built Battery for alarms	✓
I:E Ratio	Preset (1:2)
Oxygen Concentration (Air mix)	60 or 100%
Minute Volume with 60% O ₂	3–20 Ltr/min
Minute Volume with 100% O ₂	2–15 Ltr/min
Breathing Frequency (Adjustable)	6–30 bpm
Add on PEEP (Optional)	0-20 cmH ₂ O
Pressure Manometer	(-)20 to 100 cmH ₂ O
Noise	<65 db
Cylinder Time - 3 Ltr. cylinder when fully charged (using MV of 6 l/m)	>60 mi
Driving Gas Pressure	280-600 kPa
Electronically Controlled Alarm System	✓
Low Pressure Alarm (Apnea Alarm)	✓
High Pressure Alarm (Barotrauma)	✓
Low Battery Alarm	✓
Low Gas Supply Alarm	✓
Ventilation Cycle Indication	✓
Alarm Silence up to 120 Sec.	✓
Dimensions (mm) W x H x D	257 x 135 x 152
Weight	4.4 Kg
Storage Temperature	0°C-50°C
Operating Temperature	0°C-50°C
Storage Atmospheric Pressure	50-110kPa
Operating Atmospheric Pressure	70-110kPa
Wall Mount	Optional

Standard Accessories

- Ventilator Main Unit 1 Set
- Hose System 1 Set
- Regulator with Flowmeter & Gauge 1 Set
- Oxygen Cylinder 1 Piece
- Frame Work and Dust Proof Cover
- Breathing Hose with Expiratory Valve
- NIV Mask 1 Piece
- Suction Tube & Bottle 1 Set
- Suction Catheter with Suction Cannula
- Cylinder Filling Attachment 1 Set



Customized Emergency Resuscitation Kit (For details contact your local Sales Representative)



Manufactured in India by

Allied Medical Limited

76-77, Udyog Vihar, Phase IV,

Gurugram - 122 015, Haryana, INDIA

Phone : +91 124 4111444 Mobile : +91 9667462828

Toll Free: 1800 102 7879

E-mail : sales@alliedmed.co.in Website : www.alliedmed.co.in Design & Technology Partner



Meditec International England Limited

E-mail: sales@meditecengland.co.uk Website: www.meditecengland.co.uk #55000326R2 Ver. 22.9