

Product Specifications -

| PARAMETERS | CARDIART GENX12i+ | CARDIART GENX12i |
|----------------------------------|---|--|
| Display | 8" Touch Color TFT LCD with 800x480 Pixel Resolution and Adjustable Tilt Angle | 9" Color TFT LCD with 800x480 Pixel Resolution and Fixed Tilt Angle |
| Keyboard | Silicone Rubber keypad with tactile feedback - 69 keys & 3 LED indicators | |
| Indicators | Mains Connection, Battery Charging, Battery Low & System Errors | |
| Audible Beep | Heart Rate and Key Press | |
| Startup Time | Less than 4 seconds | |
| Record Storage | 800 ECGs in internal memory | 400 ECGs in internal memory |
| Recording system | Thermal printer, 8 dots/mm, 216mm usable print width. | |
| Paper transport speed | 5mm/sec or 6.25mm/sec or 12.5mm/sec or 25mm/sec or 50mm/sec | |
| Thermal Paper | Roll with pre-printed grid & perforation: Width 216mm, Length 15m Width 210mm, Length 15m Z-fold with pre-printed grid & perforation: Width 210mm x 295 mm, 100 sheets | |
| Print channel | 12 Channels | |
| Print formats | Manual: 3x1, 6x1, 12x1 Auto: 12x1, 6x2, 3x4, 6x2 +1 Rhythm, 3x4 +1 Rhythm, 3x4 +3 Rhythm Long Lead: 1 lead for 60 second duration, 3 leads for 20 second durations | |
| PC connectivity | ECG transfer to PC through RT-VIEW SOFTWARE(Optional) | |
| Paper Save Feature | Simultaneous ECG acquisition and saving | |
| Paperless Workflow | ECG Data Export in multiple formats | |
| HL7 Integration | HL7 3.0 Export on USB, Ethernet interfaces. | |
| FTP Server Upload | ECG Data upload onto selectable ftp servers in PDF, RAW & HL7 formats | |
| Operating Temperature | +10 to +40°C | |
| Relative Humidity | Upto 95% RH non-condensing | |
| Storage/Transport Temperature | -10 to +50°C | |
| Safety Classification | Class I with internal power supply | |
| Degree of protection | Type CF | |
| Dimension | Approx. 420mm x 320mm x 102mm (length x width x height) | Approx. 420mm x 320mm x 128mm (length x width x height) |
| Weight | Approx. 4.5 Kgs (Including battery, without paper) | |
| Standard Accessories | Patient Cable: 1 No. Limb Electrodes: 4 Nos. Chest Electrodes: 6 Nos. Thermal Paper Roll / Thermal Paper Z-Fold: 1 No. User's Manual: 1 No. Power Cord: 1No. Earth Cable: 1 No. | |
| | | *Technical specification subject to c |

 ${}^{\star}\text{Technical specification subject to change}$

ISO 13485:2016 CERTIFIED COMPANY ISO 9001:2015 CERTIFIED COMPANY

BPL Medical Technologies Private Limited

Regd. Office: 11th KM, Bannerghatta Road, Arakere, Bangalore - 560076, India. Toll Free: 1800-4252355 Website: www.bplmedicaltechnologies.com For Enquiries: sales.medical@bpl.in CIN: U33110KA2012PTC067282







